


Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved. In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△					△					
△					△					
APPLICABLE STANDARD										
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C			STORAGE TEMPERATURE RANGE	— °C TO — °C				
	VOLTAGE	AC 250 V			OPERATING HUMIDITY RANGE	— % TO — %				
	CURRENT	0.5 A			APPLICABLE CABLE	—				
SPECIFICATIONS										
ITEM		TEST METHOD			REQUIREMENTS			QT/AT		
CONSTRUCTION										
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			○ ○		
MARKING		CONFIRMED VISUALLY.						○ ○		
ELECTRIC CHARACTERISTICS										
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).			① 35 mΩ MAX.			○ ○		
INSULATION RESISTANCE		500V DC.			500 MΩ MIN.			○ ○		
VOLTAGE PROOF		500 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.			○ ○		
MECHANICAL CHARACTERISTICS										
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE		40 N MIN.		○	
					EXTRACTION FORCE		147 N MAX.		—	
MECHANICAL OPERATION		1000 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: ① 35mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.					○
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, - m/s ² AT 2 h, FOR 3 DIRECTIONS.			NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.					○
SHOCK		490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIME FOR 6 DIRECTION.								○
ENVIRONMENTAL CHARACTERISTICS										
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → 5~35 → 85 → 5~35 °C TIME 30 → 2~3 → 30 → 2~3 min UNDER 5 CYCLES.			NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.					○
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 °C, 90~95 %RH, 96 h.			① INSULATION RESISTANCE AT HIGH HUMIDITY 1 MΩ MIN. AT DRY 100 MΩ MIN. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.					○
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.			NO HEAVY CORROSION.					○
NOTE ① CONTACT RESISTANCE TEST POSITION.										
										
REMARKS				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED		
				<i>F. Saniguchi</i>	<i>F. Saniguchi</i>	<i>Y. Enami</i>	<i>S. Matsuyuki</i>			
				02.08.19	02.08.19	02.08.19	02.08.19			
Unless otherwise specified, refer to JIS C 5402.										
Note QT:Qualification Test AT:Assurance Test ○:Applicable Test										
HS HIROSE ELECTRIC CO., LTD.				SPECIFICATION SHEET			PART NO. DX40M-100P			
CODE NO.(OLD)		DRAWING NO.			PART NO.					
GL		ELC4-041449			CL230-5039-1					
									1/1	

TO
Q1

