



SIGN	DATE	DESCRIPTION	APPROVER
△	10/14/09	The dimension changed from 3.91to3.70	Kind
△	10/14/09	The dimension changed from 3.20to3.30+0.20/-0	Kind
△	05/15/14	The dimension changed from 3.30+0.05/-0.05 to 3.50+0.10/-0.10	Chen Bo
△	01/11/16	Delete the dimension 78° & change the left view to right view	Evan
△	01/11/16	Change the dimension from 0.30 to 0.30 <sup>+0.05</sup> <sub>-0.18</sub>	Evan
△	01/11/16	Change the dimension from 15.04 to 14.05 <sup>+0.32</sup> <sub>-0</sub>	Evan
△	01/11/16	Change the dimension from 3.00 to 3.0	Evan
△	01/11/16	Change the dimension from 24.55 to 25.0	Evan
△	01/11/16	Change the dimension from 3.70±0.05 to 3.70 <sup>+0.05</sup> <sub>-0.15</sub>	Evan

**THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!**

- NOTE:  
 1.MATERIAL:  
 ● Item a Wire guard:PHBZ(T=0.3mm),Tin plated.  
 ● Item b Spring : Stainless steel(T=0.15mm)  
 ● Male contact is inserted into the plug housing KI 3.81 after crimping the conductor, for conductors from 0.5 to 1.0 mm<sup>2</sup>  
 ● Critical dimension: ▽

<b>ANYTEK</b>				<b>CUSTOMER COPY</b>			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		AO 3.81 脚子彈片成品 ( wire range 0.5~1.0mm <sup>2</sup> )					
PART NO.		A000000000000G			DWG NO.		8A00001
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Evan 01/29-16	Chen Bo 05/15/14			X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
				SHEET: 01/01		UNIT: mm SCALE: NONE REV.: E	